

End Use Classification (BS 5808: 1991): GD/U, General Domestic Use

Prolongs life of carpets

Guaranteed for the serviceable lifetime of the carpet when used in the recommended location

Roll size: 1.37 m x 11.0 m

Specification	BS Requirements	Result	Method
Nominal square weight		2545 g/m ² (75 oz/sq yd)	
Nominal thickness		8.25 mm	BS 4051
Mean original thickness from nominal thickness	Maximum 12%	3.0%	
Difference between max. & min. original thicknesses	Maximum 3mm	0.5 mm	
Work of compression	Minimum 50 J/m ² after dynamic loading for 1000 impacts	85 J/m ²	BS 4098 & BS 4052
Compression after dynamic loading	Minimum 2mm, maximum 7mm after 1000 impacts	6.2 mm	
Retention of work of compression	Minimum 40% of original after 1000 impacts	70 %	
Breaking strength - length	Minimum 40N	185 N	BS 2576
Breaking strength - width		110 N	
Extension under force - length	Maximum 10% @ 40N	3.1 %	
Extension under force - width		0.9 %	
Loss in thickness after dynamic loading	Maximum 15% after 1000 impacts	6.6 %	BS 4052
Loss in thickness after static loading	Maximum 15% after 24hrs loading & recovery	8.2 %	BS 4939
Resistance to cracking	Not greater than 50mm	Pass	BS 5808
Odour		No objectionable odour	
Colour and appearance		Green sponge rubber waffle with printed Textron paper backing	

Item Code TAXD110013

Issue No. 3

Issue Date 29-Nov-05

Page No. 1 of 1

Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Interfloor Ltd, Broadway, Haslingden, Rossendale, Lancashire. BB4 4LS.

Tel: +44(0)1706 213131 Fax: +44(0)1706 260800 Email: technical@interfloor.com Web: www.interfloor.com