

## STIKATAK GRIPPER ADHESIVE S7512



## Safety Data Sheet

## 1 Identification of the Substance/Preparation and Company

PRODUCT NAME: GRIPPER ADHESIVE  
PRODUCT CODE: S751/S7512

Reviewed on 25.03.2010

Interfloor Ltd.  
Broadway,  
Haslingden,  
Rossendale,  
Lancashire  
BB4 4LS

Tel: 01706 213131  
Fax: 01706 214737

[www.stikatak.co.uk](http://www.stikatak.co.uk)  
[www.interfloor.com](http://www.interfloor.com)

## 2 Hazards identification:

**Main hazards:** Highly flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Other hazards:** In use may form flammable/explosive vapour-air mixture

## 3 Composition/information on ingredients

Hazardous ingredients			
CAS: 78-93-3 EINECS: 201-159-0	Ethyl Methyl Ketone	Xi, F; R 11-36-66-67	10-30%
	Naphtha (petroleum) hydrotreated light	Xn, Xi, F, N; R 11-38-51/53-65-67	5-10%
CAS: 64742-48-9	Naphtha (petroleum) hydrotreated heavy	Xn, Xi, F, N; R 11-38-51/53-65-67	5-10%

## 4 First aid measures

## Symptoms

**Skin contact:** There may be mild irritation at the site of contact.  
**Eye contact:** There may be irritation and redness  
**Ingestion:** There may be irritation of the throat  
**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

## Action

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to the skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.  
**Eye contact:** Bathe eye with running water for 10 minutes. Consult a doctor.  
**Ingestion:** Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.  
**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

## 5 Fire fighting measures

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.  
**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. May form flammable/explosive dust-air mixture.  
**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## STIKATAK GRIPPER ADHESIVE S7512

### 6 Accidental release measures

<b>Personal precautions:</b>	Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition.
<b>Environmental precautions:</b>	Do not discharge into drains or rivers.
<b>Clean-up procedures:</b>	Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up that may produce sparks.

### 7 Handling and storage

<b>Handling requirements:</b>	Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area.
<b>Storage conditions:</b>	Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.
<b>Suitable packaging:</b>	Must only be kept in original packaging.

### 8 Exposure controls and personal protection

<b>Hazardous ingredients:</b>	ETHYL METHYL KETONE WEL ( 8hr TWA): 600mg/m <sup>3</sup> WEL (15 min STEL): 899mg/m <sup>3</sup>
<b>Engineering measures:</b>	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not sources of ignition.
<b>Respiratory protection:</b>	Gas/vapour filter, type A; organic vapours (EN141), must be worn if vapour concentration is above OES or if ventilation is poor.
<b>Hand protection:</b>	Protective gloves.
<b>Eye protection:</b>	Safety glasses. Ensure eye bath is to hand.
<b>Skin protection:</b>	Protective clothing.

### 9 Physical and chemical properties:

<b>Form:</b>	<b>Paste.</b>
<b>Colour:</b>	Beige
<b>Odour:</b>	Pungent
<b>Evaporation rate:</b>	Fast
<b>Oxidising:</b>	Non-oxidising (by EC criteria)
<b>Solubility in water:</b>	Insoluble
<b>Also soluble in:</b>	Most organic solvents
<b>Viscosity:</b>	Highly viscous
<b>Boiling point/range:</b>	64°C
<b>Flash point:</b>	-10°C
<b>Relative density:</b>	1.16
<b>VOC g/l:</b>	30%

### 10 Stability and reactivity

<b>Stability:</b>	Stable under normal conditions. Stable at room temperature.
<b>Conditions to avoid:</b>	Heat. Hot surfaces. Sources of ignition. Flames.
<b>Materials to avoid:</b>	Strong oxidizing agents. Strong acids.
<b>Haz. Decomp. prods:</b>	In combustion emits toxic fumes.

### 11 Toxicological information

<b>Acute toxicity:</b>	STIKATAK GRIPPER ADHESIVE S7512 IHL RAT LC50 SKN
<b>Routes of exposure:</b>	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

### 12 Ecological information:

<b>Persistence and degradability:</b>	No data available
<b>Bioaccumulative potential:</b>	No data available

## STIKATAK GRIPPER ADHESIVE S7512

**Other adverse effects:** Harmful to aquatic organisms.

---

### 13 Disposal considerations

**Disposal operations:** Dispose of according to local or national legislation.  
**NB:** The user's attention is drawn to the possible existence of regional or national regulations

---

### 14 Transport information

#### ADR/RID

<b>ADR Class:</b>	3 Flammable liquids.	<b>UN-Number:</b>	1133
<b>Packaging group:</b>	II	<b>Classification code:</b>	F1
<b>Shipping name:</b>	ADHESIVES		
<b>Labelling</b>	3	<b>Hazard ID no:</b>	33



#### IMDG/IMO

<b>UN Number:</b>	1133	<b>Class:</b>	3
<b>Packaging group:</b>	II	<b>EmS</b>	F-E,S-D
<b>Marine pollutant:</b>	No		
<b>Labelling</b>	3		

#### IATA/ ICAO

<b>UN Number:</b>	1133	<b>Class:</b>	3
<b>Packaging group:</b>	II		
<b>Packing instructions:</b>	305(P&CA); 307(CAO)		
<b>Labelling</b>	3		

### 15 Regulatory information

**Hazard symbols:** Highly flammable



**Risk phrases:** R11: Highly flammable.  
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:** S2: Keep out of the reach of children.  
S7/9: Keep container tightly closed and in a well-ventilated place.  
S16: Keep away from sources of ignition - No smoking.  
S51: Use only in well-ventilated areas  
S23: Do not breathe vapour.  
S33: Take precautionary measures against static discharges.  
S46: If swallowed, seek medical advice immediately and show this container or label.  
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

---

### 16 Other information:

## STIKATAK GRIPPER ADHESIVE S7512

**Risk phrases used in s.3:** R11: Highly flammable.  
R36: Irritating to eyes  
R38: Irritating to skin.  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65: Harmful: may cause lung damage if swallowed.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above data is based on our present knowledge. However, it shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.  
The information provided about the product on this Safety Sheet has been compiled from knowledge of the individual constituent.  
The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer.

**Department issuing data specification sheet:** Quality Control

**Contact:**

Scott Yarrow  
Tel 0208 839 4405  
Fax 0208 842 1387  
e-mail: scottymarow@stikatak.co.uk