

Underlay Technical Specification

Item Code: TADUP08013

Issue Date: 04/03/2019

Issue No. 7

Crumb Rubber

**Suitable for the single -stick, double-stick and stretch-fit installation of carpets
Not suitable for single-stick applications in areas greater than 33m²**

End Use Classification (BS 5808: 1991): HC/U, Heavy Contract Use



Standard Specifications

Nominal square weight†	4000 g/m ² (118 oz/yd ²)
Nominal roll weight†	43.84 kg
Roll area*	10.96m ² (1.37m x 8.00m)


BS 5808: 1991 / EN14499

End Use Classification	HC/U, Heavy Contract Use	
Nominal thickness†	9.20mm	BS 4051
Mean original thickness from nominal thickness (max. 12%)	3.0 %	BS 4051
Difference between max. & min. original thickness (max. 3mm)	0.4 mm	BS 4051
Work of compression Minimum 50 J/m ²	98 J/m ²	BS 4098 & BS 4052
Retention of work of compression (min 40%)	100 %	BS 4098 & BS 4052
Compression after dynamic loading	2.2 mm	BS 4098 & BS 4052
Loss in thickness after dynamic loading (max 15%)	2.1 %	BS 4052
Loss in thickness after static loading (max 15%)	2.8 %	BS 4939
Breaking strength (length/width) min. 30N	710N / 332N	BSEN13934
Extension under force (length/width) max. 15% @ 30N	1.0% / 0.5%	
Resistance to cracking (not greater than 50mm)	Pass	BS 5808

Flammability

Reaction to fire classification (Tested in conjunction with Axminster 80:20 carpet)	Cfl-s1	Tested to ENISO9239-1 & 11925-2, rated to EN13501-1
Russian GOST FR Test	Classification KM5	GOST 30244-94, GOST 30402-96 GOST 51032-97, GOST 12.1.044-89 (item 4.18) GOST 12.1.044-89 (item 4.20)

Certification



Guarantee

Guaranteed for the serviceable lifetime of the carpet when used in accordance with the End Use Classification.

Notes

* The nominal roll dimensions have been quoted. These may vary slightly, but will still equate to the area quoted. This does not constitute a manufacturing specification. It details important performance and physical characteristics only.

† ±10%

‡ Value derived from similar product test results

Underlay Technical Specification

Item Code: TADUP08013

Issue Date: 04/03/2019

Issue No. 7



Other Specifications

Odour	No objectionable odour	
Antimicrobial and mildew resistant	Yes	
Colour / backing	Black / Bacloc backing	
Packaging	Green film / black print	
Thermal resistance	1.55 togs	BS 4745
Impact sound reduction (Delta Lw)	31 dB	BSEN ISO 140-8: 1998 and BSEN ISO 717-2: 1997

GREEN CREDENTIALS


Green Features	Description	LEED Programme
Recyclable	At the end of the underlays useful life it can be 100% recycled	MR 2.0: Points Available It can be recycled
Recycled Content	Contains not less than 65% post-consumer recycled material	MR 4.0: Points Available Recycled Content
Indoor Air Quality	Meets or exceeds the industry standard for indoor air quality as established by the CRI Green Label Programme	IEQ 4.3: Points Available Product is Green Label Plus Certified
Regional Materials	Production Facility Haslingden B4 4LS, UK Where used within 500 miles of Production Facility	MR 5.0: Points Available

LEED points must be considered along with other building components and must be determined by the specifier/architect or LEED accredited professional

Recycled Content

Post Consumer	65%
Pre Consumer	0%
Virgin	35%

Certification



Guarantee

Guaranteed for the serviceable lifetime of the carpet when used in accordance with the End Use Classification.

Notes

- * The nominal roll dimensions have been quoted. These may vary slightly, but will still equate to the area quoted. This does not constitute a manufacturing specification. It details important performance and physical characteristics only.
- † ±10%
- ‡ Value derived from similar product test results