



STIKATAK 200

Page: 1

Compilation date: 06/02/2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: STIKATAK 200

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Interfloor Ltd

Broadway Haslingden Rossendale Lancashire BB4 4LS

United Kingdom

Tel: 01706 213131 **Fax:** 01706 224915

Email: chris.mcgilvray@interfloor.com

1.4. Emergency telephone number

Emergency tel: 01706 213131

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; -: EUH208

Most important adverse effects: Contains biocide based on 1,2 benzisothiazol-3(2h)-one and 2 methyllisothiazol-3(2h)-

one, fungicide based on 2-octyl-2h-isothiazol-3-one. May produce an allergic reaction. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long

lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains biocide based on 1,2 benzisothiazol-3(2h)-one and 2

methyllisothiazol-3(2h)-one, fungicide based on 2-octyl-2h-isothiazol-3-one. May

produce an allergic reaction.

STIKATAK 200

Page: 2

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P264: Wash hands thoroughly after handling.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P321: Specific treatment (see instructions on this label).

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

POLYMERIC AQUEOUS DISPERSION (P)

EINECS CAS		PBT / WEL	CLP Classification	Percent	
-	-	-	Eye Irrit. 2: H319	30-50%	
CALCIUM CARBONATE					
-	1317-65-3	Substance with a Community workplace exposure limit.	-	10-30%	

POTASSIUM HYDROXIDE

215-181-3	1310-58-3	-	Acute Tox. 4: H302; Skin Corr. 1A:	<1%
			H314	

BIOCIDE BASED ON 1,2 BENZISOTHIAZOL-3(2H)-ONE AND 2 METHYLLISOTHIAZOL-3(2H)-ONE

-	-	-	Aquatic Chronic 3: H412; Eye Dam. 1:	<1%
			H318; Skin Sens. 1: H317	

STIKATAK 200

Page: 3

FUNGICIDE BASED ON 2-OCTYL-2H-ISOTHIAZOL-3-ONE

-	-	-	Skin Corr. 1A: H314; Eye Dam. 1:	<1%
			H318; Skin Sens. 1: H317; Aquatic	
			Acute 1: H400; Aquatic Chronic 2:	
			H411	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Do not

create dust.

[cont...]

STIKATAK 200

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

POLYMERIC AQUEOUS DISPERSION (P)

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	25	-	-	-

CALCIUM CARBONATE

UK	10mg/m3	-	-	-
----	---------	---	---	---

POTASSIUM HYDROXIDE

UK	-	2 mg/m3	-	-

DNEL/PNEC Values

Hazardous ingredients:

POLYMERIC AQUEOUS DISPERSION (P)

Type	Exposure	Value	Population	Effect
1 9 0 0	LAPOSUIC	v aluc	i opulation	LIICO

STIKATAK 200

Page: 5

DNEL	Inhalation	47	Workers	Systemic
DNEL	Dermal	68	Workers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory

protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Solid

Colour: Off-white

Odour: Barely perceptible odour

Evaporation rate: Not applicable.

Oxidising: Not applicable.

Solubility in water: Not applicable.

Viscosity: Not applicable.

Boiling point/range°C: >35 **Melting point/range°C:** Not applicable.

Flammability limits %: lower: Not applicable. upper: Not applicable.

Flash point°C: >93 Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: Not applicable. Vapour pressure: Not applicable.

Relative density: Not applicable. pH: Approx. 7

VOC g/l: Not applicable.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

STIKATAK 200

Page: 6

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

POLYMERIC AQUEOUS DISPERSION (P)

ORAL	RAT	LD50	0.0011	mg/l	
0.0.			0.00.	9, .	

POTASSIUM HYDROXIDE

ORL	RAT	LD50	273	mg/kg
JOINE	1 1 1 1 1		210	111g/ Ng

BIOCIDE BASED ON 1,2 BENZISOTHIAZOL-3(2H)-ONE AND 2 METHYLLISOTHIAZOL-3(2H)-ONE

DERMAL	RAT	LD50	>2000	mg/kg
DUST/MIST	RAT	LD50	5.71	mg/l
ORAL	RAT	LD50	>2500	mg/kg

FUNGICIDE BASED ON 2-OCTYL-2H-ISOTHIAZOL-3-ONE

DERMAL	-	-	>5000	mg/kg
DUST/MIST	-	-	1.7	mg/l
ORAL	RAT	-	>2000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

STIKATAK 200

Page: 7

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

BIOCIDE BASED ON 1,2 BENZISOTHIAZOL-3(2H)-ONE AND 2 METHYLLISOTHIAZOL-3(2H)-ONE

Daphnia magna	48H EC50	32	mg/l
Daprilla Illaglia	4011 LO30	32	1119/1

FUNGICIDE BASED ON 2-OCTYL-2H-ISOTHIAZOL-3-ONE

ALGAE	72H ErC50	0.004	mg/l
Daphnia magna	96H ErC50	0.42	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	72H ErC50	0.036	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3077

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

STIKATAK 200

Page: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.