



STIKATAK 900

Page: 1

Compilation date: 06/02/2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: STIKATAK 900

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: Interfloor Ltd

Broadway
Haslingden
Rossendale
Lancashire
BB4 4LS

United Kingdom

Tel: 01706 213131 **Fax:** 01706 224915

Email: chris.mcgilvray@interfloor.com

1.4. Emergency telephone number

Emergency tel: 01706 213131

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; -: EUH208

Most important adverse effects: Contains biocide b. May produce an allergic reaction. Causes skin irritation.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains biocide b. May produce an allergic reaction.

H315: Causes skin irritation.

Hazard pictograms: GHS07: Exclamation mark



STIKATAK 900

Page: 2

Signal words: Warning

Precautionary statements: P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/.
P321: Specific treatment (see instructions on this label).
P332+313: If skin irritation occurs: Get medical attention.

P362: Take off contaminated clothing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

CALCIUM CARBONATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	1317-65-3	Substance with a Community	-	30-50%
		workplace exposure limit.		

POLYMERIC AQEOUS DISPERSION (L)

-	-	Substance with a Community	-	10-30%	
		workplace exposure limit.			

WHITE SPIRIT

-	-	-	Flam. Liq. 3: H226; Aquatic Chronic 3:	1-10%
			H412; Skin Irrit. 2: H315; Asp. Tox. 1:	
			H304	

BIOCIDE BASED ON 1,2 BENZISOTHIAZOL-3(2H)-ONE AND 2 METHYLLISOTHIAZOL-3(2H)-ONE

-	-	-	Aquatic Chronic 3: H412; Eye Dam. 1:	<1%
			H318; Skin Sens. 1: H317	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

STIKATAK 900

Page: 3

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not

create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of dust in the air.

STIKATAK 900

Page: 4

[cont...]

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

CALCIUM CARBONATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	10mg/m3	-	-	-

POLYMERIC AQEOUS DISPERSION (L)

UK	2.5mg/m3	2.5mg/m3	-	-
----	----------	----------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory

protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Solid

Colour: Off-white

Odour: Barely perceptible odour

Evaporation rate: Slow

Oxidising: Not applicable.

Solubility in water: Soluble

Viscosity: Viscous

Relative density: Not applicable.

Boiling point/range°C: >35 **Melting point/range°C:** Not applicable.

Flammability limits %: lower: Not applicable. upper: Not applicable.

Flash point°C: >93 Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: Not applicable. Vapour pressure: Not applicable.

The applicable.

STIKATAK 900

Page: 5

pH: Approx. 7

VOC g/l: Not applicable.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

WHITE SPIRIT

DERMAL	RBT	-	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

BIOCIDE BASED ON 1,2 BENZISOTHIAZOL-3(2H)-ONE AND 2 METHYLLISOTHIAZOL-3(2H)-ONE

DERMAL	RAT	LD50	>2000	mg/kg
DUST/MIST	RAT	LD50	5.71	mg/l
ORAL	RAT	LD50	>2500	mg/kg

Relevant hazards for product:

Hazard Rout	e Basis
-------------	---------

STIKATAK 900

Page: 6

Skin corrosion/irritation	DRM	Hazardous: calculated
---------------------------	-----	-----------------------

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

WHITE SPIRIT

ALGAE	48H EC50	10<>100	mg/l
FISH	48H EC50	10<>100	mg/l

BIOCIDE BASED ON 1,2 BENZISOTHIAZOL-3(2H)-ONE AND 2 METHYLLISOTHIAZOL-3(2H)-ONE

Dankaia maama	4011 5050	00	/1	
Daphnia magna	48H EC50	32	mg/l	ı

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

STIKATAK 900

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN3077

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E
Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

STIKATAK 900

Page: 8

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.