


Underlay Technical Specification

Item Code: TALVTMULTIFIT

Issue Date: 23/04/2018

Issue No. 1



Sponge Rubber

Suitable for the installation of luxury vinyl tile flooring


Standard Specifications

| | | |
|---|--|---|
| Thickness | 1.50 mm | EN 823 + Annex A.3.1 |
| Nominal square weight † | 2500 g/m ² (74 oz/yd ²) | |
| Nominal roll weight † | 25.00 kg | |
| Roll area* | 10.00 m ² (7.30m x 1.37m) | |
| Reflected walking sound (RWS) | 44 dB | DIN EN 16205 |
| Impact sound | up to 14 dB | EN ISO 10140-3 and ISO 717-2 |
| Thermal resistance | 0.12 togs | BS 4745 |
| Thermal resistance | 0.012 m ² K/W | EN 12667 or EN 12664 |
| Compressive strength | 503 kPa | EN 826 + Annex A.3.7 |
| Compressive Creep resistance | Awaiting results | EN 1606 + Annex A.3.8 |
| Dynamic load resistance | >1000,000 cycles | EN 13793 + Annex A.3.9 |
| Resistance to impact by large diameter ball | 1800 mm | EN 13329 annex F and EN 438 chapt. 21 |
| Punctual Conformability | 0.55mm | EN 16354 |
| Reaction-to-fire (RTF) | Bfl-s1 | BS EN 13501-1 - Table 2 (underlay plus laminate in end-use conditions) |

Other Specifications

| | |
|------------------------------------|--|
| Odour | No objectionable odour |
| Antimicrobial and mildew resistant | Yes |
| Colour / backing | Black nonwoven facing / white nonwoven backing |
| Packaging | Clear, with printed insert |

Certification



Guarantee

Guaranteed for the serviceable lifetime of the flooring.

Notes

* The nominal roll dimensions have been quoted. These may vary slightly, but will still equate to the area quoted. This does not constitute a manufacturing specification. It details important performance and physical characteristics only.


† ±5%

Underlay Technical Specification

Item Code: TALVTMULTIFIT

Issue Date: 23/04/2018

Issue No. 1



Responsibly made

Duralay LVT Underlay is free from plasticisers, asbestos, formaldehyde, halogens and heavy metals. It complies with the French afsset A+guidelines on VOCs, and meets and the German AgBB scheme standards.

Ecological Aspects

This product is solvent free and does not contain any other ozone depleting substances. The renewable resources used in the product do not compete with food crops (during growth).

Health & Safety

This product does not require any special health and safety measures to be taken. When laying the flooring, it is essential to adhere to the manufacturer's advice on protection.

Processing


The approval of the flooring and adhesive manufacturers must be obtained prior to the installation of the product. Please refer to the LVT manufacturer's installation guidelines before fitting.

GREEN CREDENTIALS

| Green Features | Description | LEED Programme |
|--------------------|---|---|
| Recyclable | At the end of the underlays useful life it can be 100% recycled | MR 2.0: Points Available It can be recycled |
| Recycled Content | Contains not less than 3% pre-consumer recycled material | MR 4.0: Points Available Recycled Content |
| Indoor Air Quality | Meets or exceeds the industry standard for indoor air quality as established by the CRI Green Label Programme | IEQ 4.3: Points Available Product is Green Label Certified |
| Regional Materials | Production Facility Haslingden B4 4LS, UK Where used within 500 miles of Production Facility | MR 5.0: Points Available |

LEED points must be considered along with other building components and must be determined by the specifier/architect or LEED accredited professional

Certification



Guarantee

Guaranteed for the serviceable lifetime of the flooring.

Notes

* The nominal roll dimensions have been quoted. These may vary slightly, but will still equate to the area quoted. This does not constitute a manufacturing specification. It details important performance and physical characteristics only.

† ±5%