




# **Underlay Technical Specification**

Item Code: TARENU9160

Issue Date: 12/10/2023

Issue No.2








## Certification







## Guarantee

Guaranteed for the serviceable lifetime of the carpet when used in accordance with the End Use Classification.

Polyurethane Rebond

Suitable for stretch-fit installation of carpets

End Use Classification (BS 5808: 1991 / BS EN 14499 : 2015): L/U, Luxury Use

Standard Specifications\*

Nominal density	160 kg/m³	
Nominal square weight	1528 g/m²	
Nominal roll weight	23.00 kg	
Nominal roll area	15.07m² (1.37m x 11.0m)	
Nominal thickness	9.00mm	ISO 1765

BS 5808: 1991 / EN14499 : 2015

End Use Classification	L/U, Luxury Use	
Work of compression (Min. 50 J/m² Max. 200 J/m²)	>140 J/m²	BS 4098 & ISO 2094
Retention of work of compression (min 40%)	>90 %	BS 4098 & ISO 2094
Loss in thickness after Dynamic loading (max 15%)	<5 %	BS 4052 & ISO 2094
Loss in thickness after static loading (max 15%)	<5 %	ISO 3415/3416 & BS 4939
Breaking strength (length/width) min. 40N	>90N / >40N	EN ISO 13394 BS 2576
Extension under force (length/width) max. 15%@ 30N	<10% / <10%	211100 10004 20 2010
Resistance to cracking (not greater than 50mm)	Pass	EN 14499 & BS 5808
resistance to cracking (not greater than somm)	1 833	EN 14499 & BS 3000

Flammability

Hot metal nut test (tested in Interfloor laboratory)

Low radius of effects of ignition

BS 4790 & BS 5287

Other Specifications

Odour	No objectionable odour		
Antimicrobial and mildew resistant	Pass ASTM G21		
Colour / backing	Green bio-based film / 100% recycled stictchet kraft paper backing printed with vegetable-based ink		
Packaging	White bio-based or 100% post-consumer waste film / green ink		
Thermal resistance	2.54 togs BS 4745		
Impact sound reduction (Delta Lw)	41dB BS EN ISO 10140 rated to BS EN ISO 717		
Emissions (US Carpet & Rug Institute)	Meets low VOC emission criteria		
Emissions (GEV Emicode)	Very low emission EC1 PLUS		
French VOC Emission Regulations	Complies A+		

## **GREEN CREDENTIALS**

Recycled Content (97.9	9%)	Sustainable Content (0.4%)		Other (1.7%)†		
Post Consumer Foam	97%	Bio-based Film	0.4%		Other	1.7%
Recycled Paper	0.9%					

<sup>†</sup> Sustainable options currently under development.

#### Notes

- \* The nominal roll dimensions have been quoted. These may vary slightly but will comply with the requirements of BS EN 14499:2015
- <sup>‡</sup> Value derived from similar product test results

THIS PRODUCT IS PRODUCED IN A FACILITY ACCREDITED TO ISO 9001, 14001 & 45001



Interfloor Ltd., Broadway, Haslingden, Rossendale, Lancashire, BB4 4LS.
Tel: +44(0)1706 213131 Fax: +44(0)1706 214737 Web: www.interfloor.com
International Enquiries: Telephone: +44(0)1706 238825 Fax: +44(0)1706 225114