

Safety Data Sheet

According to EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830.

Revision date: 28/04/2021

Version No. 5

Trade name: STK100 Acrylic Flooring Adhesive

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1 Product identifier**

Product name: STK100 Acrylic Flooring Adhesive

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses: Flooring Adhesive

Uses advised against: None known

**1.3 Details of the supplier of the safety data sheet**

Supplier: Interfloor Ltd.  
Broadway  
Haslingden  
Rossendale  
Lancashire  
BB4 4LS  
Tel: 01706 213131  
Fax: 01706 224915  
Email: [chris.mcgilvray@interfloor.com](mailto:chris.mcgilvray@interfloor.com)

**1.4 Emergency telephone number**

+44 (0)1706 213131 (Mon-Fri) 09:00-17:00 Hrs

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture**

Classification (EC1272/2008)

Physical hazards: Not Classified

Health hazards: Not Classified

Environmental hazards: Not Classified

**2.2 Label elements**

Supplemental labelling EUH208 Contains 5-chloro-2-methyl-4-iso-thiazolin-3-one (EC no. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6). May produce an allergic reaction.

**2.3 Other hazards**

Not classified as hazardous for transport or supply.

Trade name: STK100 Acrylic Flooring Adhesive

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### **3.2 Mixtures**

Description: Adhesive.

No component of this mixture is included above the relevant concentration levels detailed within section 3.2.1 of SDS regulation 2015/830.

### **SECTION 4: FIRST AID MEASURES**

#### **4.1 Description of first aid measures**

Note Personal protective equipment for first aid responders is recommended.

Inhalation: Move to fresh air. Get medical attention if symptoms persist.

Skin Contact: Wash with soap and water. Get medical attention if symptoms persist after washing.

Eye Contact: Rinse eye immediately with plenty of water. Continue to rinse for at least 15 minutes. Get medical attention if symptoms persist.

Ingestion: Rinse mouth thoroughly with plenty of water. Drink plenty of water. Do not induce vomiting. Get medical attention if symptoms persist.

#### **4.2 Most important symptoms and effects, both acute and delayed**

May produce an allergic reaction in persons already sensitised.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

Treatment: Treat symptomatically

### **SECTION 5: FIREFIGHTING MEASURES**

#### **5.1 Extinguishing media**

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

#### **5.2 Special hazards arising from the substance or media**

No further relevant information known.

#### **5.3 Advice for firefighters**

Special fire fighting procedure: Keep containers cool by spraying with water if exposed to fire. Prevent run off water from entering drains if possible.

Special protective equipment for firefighters: Wear full protective clothing

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin, eyes or clothing.

Use protective gloves, goggles and suitable protective clothing.

Revision date: 28/04/2021

Version No. 5

Trade name: STK100 Acrylic Flooring Adhesive

## 6.2 Environment precautions

Do not discharge into drains, water courses or onto the ground.

## 6.3 Methods and material for containment and cleaning up

Small spillages: Absorb with sand or other non-combustible absorbent material.

Large spillages: Dam and absorb spillages with sand or other non-combustible material. Collect material in containers, seal securely and deliver for disposal according to local regulations.

## 6.4 Reference to other sections

Wear protective clothing as described in section 8 of this safety data sheet. For waste disposal, see section 13.

# **SECTION 7: HANDLING AND STORAGE**

## 7.1 Precautions for safe handling

Do not eat, drink or smoke when using this product.

Provide good ventilation.

Avoid spilling, skin and eye contact.

## 7.2 Conditions for safe storage, including incompatibilities

Store in tightly closed original container between 5°C and 30°C.

Avoid frost.

Avoid exposure to high temperatures or direct sunlight.

## 7.3 Specific end use(s)

The identified end uses for this product are detailed in section 1.2.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters**                      No Occupational Exposure Limit assigned.

## 8.2.1 Exposure controls

Process conditions	Provide eyewash station.
Engineering measures	Provide adequate ventilation.
Respiratory equipment	Not applicable.
Hand protection	For prolonged and repeated skin contact use protective gloves. Nitrile gloves to BSEN374 are recommended. Break through times can vary depending on thickness, use and source.
Eye protection	If there is a risk of splashing, wear approved safety goggles,
Hygiene measures	Good personal hygiene practices are recommended.

## 8.2.2

Environmental Exposure Controls              None

Thermal Hazards                                  None

Revision date: 28/04/2021

Version No. 5

Trade name: STK100 Acrylic Flooring Adhesive

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### **9.1 Information on basic physical and chemical properties**

Appearance	Viscous liquid
Colour	Off white
Odour	Typical acrylic
Odour threshold	N/A
pH-value (23°C)	6.5 (ISO 19396)
Melting point/freezing point	N/A
Initial boiling point and boiling range	Not determined
Flash point	N/A
Evaporation rate	N/A
Flammability (solid, gas)	N/A
Upper/lower flammability or explosive limits	N/A
Vapour pressure	N/A
Vapour density	N/A
Relative density (23°C)	1.28g/cm <sup>3</sup> (ISO 2811-1)
Solubility in water	Dispersible
Solubility in oil	Insoluble
Partition coefficient: n-octanol/water	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A
Viscosity (23°C)	65,000 mPa s (ISO 2555)
Explosive properties	N/A
Oxidising properties	N/A
Comments	The data provided is applicable to the mixture as a whole.

### **9.2 Other information**

Not applicable.

## **\*SECTION 10: STABILITY AND REACTIVITY**

### **10.1 Reactivity**

No specific reactivity hazards associated with this product.

### **10.2 Chemical stability**

Stable under normal temperature conditions and recommended use.

### **10.3 Possibility of hazardous reactions**

Not applicable.

### **10.4 Conditions to avoid**

Avoid frost.

Avoid exposure to high temperatures or direct sunlight.

### **10.5 Incompatible materials**

None known.

### **10.6 Hazardous decomposition products**

No dangerous decomposition products known.

Revision date: 28/04/2021

Version No. 5

Trade name: STK100 Acrylic Flooring Adhesive

## **SECTION 11: TOXICOLOGICAL INFORMATION**

### **11.1 Information on toxicological effects**

Routes of exposure:

Ingestion: Yes

Inhalation: No

Contact: No

Acute toxicity Based on the available data, the classification criteria are not met.

Skin corrosion/irritation Based on the available data, the classification criteria are not met.

Serious eye damage/irritation Based on the available data, the classification criteria are not met.

Respiratory or skin sensitization May produce an allergic reaction.

Germ cell mutagenicity Based on the available data, the classification criteria are not met.

Carcinogenicity Based on the available data, the classification criteria are not met.

Reproductive toxicity Based on the available data, the classification criteria are not met.

STOT-single exposure Based on the available data, the classification criteria are not met.

STOT-repeated exposure Based on the available data, the classification criteria are not met.

Aspiration hazard Based on the available data, the classification criteria are not met.

## **SECTION 12: ECOLOGICAL INFORMATION**

### **12.1 Toxicity**

Aquatic toxicity: No data for the mixture as a whole.

**12.2 Persistence and degradability** No data for the mixture as a whole.

**12.3 Bioaccumulative potential** No data for the mixture as a whole.

**12.4 Mobility in soil** No data for the mixture as a whole.

General notes: Do not allow product to reach ground water, water course or sewage system.

**12.5 Results of PBT and vPvB assessment** Not classified as PBT/vPvB by current EU criteria.

**12.6 Other adverse effects** No data for the mixture as a whole.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

### **13.1 Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements. Small quantities may be absorbed in sand and allowed to dry prior to disposal as low hazard waste. Larger quantities should be disposed of as controlled liquid waste via a licensed waste operator.

<b>EC waste code</b>	Dried adhesive	08 04 10
	Wet adhesive	08 04 16

## **SECTION 14: TRANSPORT INFORMATION**

General This product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

### **14.1 UN number**

### **14.2 UN proper shipping name**

### **14.3 Transport hazard class(es)**

ADR/RID class Not classified for transportation.

Transport Labels No transport warning sign require.

### **14.4 Packing group**

Revision date: 28/04/2021

Version No. 5

Trade name: STK100 Acrylic Flooring Adhesive

#### 14.5 Environmental hazards

#### 14.6 Special precautions for user

#### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC code

### **SECTION 15: REGULATORY INFORMATION**

#### **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

UK Regulatory references:	The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.
Environmental listing:	None noted.
Approved Code of Practice:	Safety data sheets for substance and preparations.
Guidance notes:	Workplace Exposure Limits EH40.
Authorisations (Title VII Regulation 1907/2006)	None noted.
Restrictions (Title VIII Regulation 1907/2006)	None noted.

#### **15.2 Chemical Safety Assessment**

No chemical safety assessment has been carried out.

### **\*SECTION 16: OTHER INFORMATION**

This information is based on our current knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Revision date:	28/04/2021
Version no:	05
Supersedes date:	21/12/2020
Labelling statement:	EUH208 Contains 5-chloro-2-methyl-4-iso-thiazolin-3-one (EC no. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6). May produce an allergic reaction.

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification Procedure
EUH208	Threshold calculation

Main bibliographic sources: Supplier SDS.  
ECHA dossiers.

SVHC (>0.1%) No

#### **Abbreviations and acronyms:**

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CLP:	Classification, Labelling, Packaging.
EC:	European Commission.
ECHA:	European Chemicals Agency.
EH40:	Health and Safety Guidance Note EH40.
EU:	European Union.
IATA:	International Air Transport Association.
ISO:	International Organization for Standardization.
IMDG:	International Maritime Code for Dangerous Goods.
PBT:	Persistent, Bioaccumulative and Toxic.
vPvB:	very Persistent and very Bioaccumulative.

Safety Data Sheet  
According to EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830.

Revision date: 28/04/2021

Version No. 5

Trade name: STK100 Acrylic Flooring Adhesive

REACH: Registration, Evaluation, Authorisation and restriction of Chemicals.  
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.  
SDS: Safety Data Sheet.  
STOT: Specific Target Organ Toxicity.  
SVHC: Substances of Very High Concern.

**\*Data compared to previous version altered.**