

interfloor

SAFETY DATA SHEET

Stikatak Carpet Stain Remover



Interfloor Limited

Broadway, Haslingden, Rossendale, Lancashire, BB4 4LS United Kingdom

Enquiries

Tel: +44 (0)1706 238810

sales@interfloor.com

interfloor.com

SAFETY DATA SHEET

Stikatak Carpet Stain Remover

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Stikatak Carpet Stain Remover
Container size 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Foam Cleaner

1.3. Details of the supplier of the safety data sheet

Supplier Interfloor Ltd
Broadway
Haslingden
Rossendale
Lancashire
BB4 4LS
Tel 01706 238 810
Fax 01706 214 737

1.4. Emergency telephone number

Emergency telephone Interfloor Ltd. ++44 (0) 1706 238 810 (Mon-Fri 09:00-17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229
Health hazards Eye Irrit. 2 - H319
Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H319 Causes serious eye irritation.

Stikatak Carpet Stain Remover

Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211 Do not spray on an open flame or other ignition source.
	P251 Do not pierce or burn, even after use.
	P264 Wash contaminated skin thoroughly after handling.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313 If eye irritation persists: Get medical advice/ attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE CAS number: 68476-85-7 EC number: 270-704-2	10-30%
Classification Flam. Gas 1A - H220 Press. Gas (Liq.) - H280	
ALCOHOLS, C9-C11, ETHOXYLATED CAS number: 68439-46-3	1-5%
Classification Acute Tox. 4 - H302 Eye Dam. 1 - H318	
1-METHOXY-2-PROPANOL CAS number: 107-98-2 EC number: 203-539-1 REACH registration number: 01-2119457435-35-0000	<1%
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336	
ISOPROPANOL CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-2119457558-25-XXXX	<1%
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	

Stikatak Carpet Stain Remover

SODIUM NITRITE			<1%
CAS number: 7632-00-0	EC number: 231-555-9	REACH registration number: 01-2119471836-27-XXXX	
M factor (Acute) = 1			
Classification			
Ox. Sol. 3 - H272			
Acute Tox. 3 - H301			
Eye Irrit. 2 - H319			
Aquatic Acute 1 - H400			

The full text for all hazard statements is displayed in Section 16.

Composition comments CAS 68476-85-7 - Petroleum Gas, The substance contains less than 0.1% w/w 1,3-butadiene, meaning that the full harmonised classification regarding Muta. 1B H340 and Carc. 1A H350 does not apply.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Rinse immediately with plenty of water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	At high concentrations, vapour can acts as an asphyxiant.
Ingestion	May cause discomfort if swallowed.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	There may be irritation and redness.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Show this safety data sheet to the doctor in attendance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray, foam, dry powder or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Specific hazards May explode when heated or when exposed to flames or sparks. The product is extremely flammable.

5.3. Advice for firefighters

Stikatak Carpet Stain Remover

Protective actions during firefighting Use water spray to reduce vapours. Containers can burst violently or explode when heated, due to excessive pressure build-up. Cool aerosol containers exposed to heat with water spray and remove container, if no risk is involved.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See section 12.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray/mists. Do not spray on a naked flame or any incandescent material. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Extremely flammable aerosol. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Do not pierce or burn, even after use.

Storage class Extremely Flammable Aerosol

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 375 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 560 mg/m³(Sk)

Stikatak Carpet Stain Remover

ISOPROPANOL

Short-term exposure limit (15-minute): WEL 1250 mg/m³ 500 ppm

Long-term exposure limit (8-hour TWA): WEL 999 mg/m³ 400 ppm

WEL = Workplace Exposure Limit.

Ingredient comments WEL = Workplace Exposure Limits

ISOPROPANOL (CAS: 67-63-0)

DNEL

Consumer - Oral; Long term systemic effects: 26 mg/kg
 Workers - Dermal; Long term systemic effects: 888 mg/kg
 Consumer - Dermal; Long term systemic effects: 319 mg/m³
 Consumer - Inhalation; Long term systemic effects: 89 mg/m³
 Workers - Inhalation; Long term systemic effects: 500 mg/m³

PNEC

- Fresh water; 140.9 mg/l
 - Sediment (Freshwater); 552 mg/kg
 - Intermittent release; 140.9 mg/l
 - Sediment (Marinewater); 552 mg/kg
 - marine water; 140.9 mg/l
 - STP; 2251 mg/l
 - Soil; 28 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Nitrile rubber. To protect hands from chemicals, gloves should comply with European Standard EN374. Frequent changes are recommended. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated.

Other skin and body protection

Provide eyewash station. Avoid contact with skin. Wear suitable coveralls to prevent exposure to the skin.

Hygiene measures

Good personal hygiene procedures should be implemented. Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet.

Stikatak Carpet Stain Remover

Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. When spraying, wear a respirator fitted with the following cartridge: Gas filter, type AX.
Thermal hazards	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
Environmental exposure controls	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	White foam.
Odour	Mild. Citrus
pH	pH (concentrated solution): 9
Melting point	No information required.
Initial boiling point and range	Liquefied petroleum gases: -40 to -2°C
Flash point	A flash point method is not available but the major hazardous component, the Propellant has a flash point of <-60°C with flammability limits of 10.9% vol. upper and 1.4% vol. lower.
Flammability (solid, gas)	No information required.
Upper/lower flammability or explosive limits	No information available.
Vapour pressure	2 - 5 bar @ 20°C
Vapour density	Not available.
Relative density	No information available.
Solubility(ies)	Soluble in water.
Auto-ignition temperature	Liquefied petroleum gases: 365°C
Viscosity	Liquid base: Kinematic viscosity ≤ 20.5 mm ² /s.
Explosive properties	Not considered to be explosive.
Oxidising properties	Not determined.

9.2. Other information

Particle size	No information required.
Volatile organic compound	This product contains a maximum VOC content of 15 %.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable under recommended transport or storage conditions.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

Stikatak Carpet Stain Remover

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No known hazardous reactions if stored under normal conditions.

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong acids.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Summary Based on available data the classification criteria are not met.

ATE oral (mg/kg) 19,665.68

Acute toxicity - dermal

Summary Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Summary Based on available data the classification criteria are not met.

Skin corrosion/irritation

Summary Based on available data the classification criteria are not met.

Serious eye damage/irritation

Summary Causes serious eye irritation.

Respiratory sensitisation

Summary Based on available data the classification criteria are not met.

Skin sensitisation

Summary Based on available data the classification criteria are not met.

Germ cell mutagenicity

Summary Based on available data the classification criteria are not met.

Carcinogenicity

Summary Based on available data the classification criteria are not met.

Reproductive toxicity

Summary Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Summary Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

Summary Based on available data the classification criteria are not met.

Aspiration hazard

Summary Based on available data the classification criteria are not met.

Stikatak Carpet Stain Remover

Toxicological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Toxicological effects	Information given is based on data of the components and of similar products.
<u>Acute toxicity - oral</u>	
Notes (oral LD₅₀)	Not applicable.
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	Not applicable.
<u>Acute toxicity - inhalation</u>	
Notes (inhalation LC₅₀)	LC ₅₀ >20 mg/l, Inhalation, Rat
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Not irritating.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Not irritating.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Not sensitising.
<u>Skin sensitisation</u>	
Skin sensitisation	Not sensitising.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	This substance has no evidence of mutagenic properties.
<u>Carcinogenicity</u>	
Carcinogenicity	Carcinogenicity in humans is not expected.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Does not contain any substances known to be toxic to reproduction.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	A single exposure may cause the following adverse effects: Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Not anticipated to present an aspiration hazard, based on chemical structure.
<u>Inhalation</u>	
Inhalation	May cause respiratory system irritation.
<u>Skin contact</u>	
Skin contact	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

Stikatak Carpet Stain Remover

Route of exposure Inhalation Skin and/or eye contact

ALCOHOLS, C9-C11, ETHOXYLATED

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,000.0

Species Rat

ISOPROPANOL

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,045.0

Species Rat

ATE oral (mg/kg) 5,045.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 12,800.0

Species Rabbit

ATE dermal (mg/kg) 12,800.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 30.0

Species Rat

ATE inhalation (vapours mg/l) 30.0

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Stikatak Carpet Stain Remover

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

SECTION 12: Ecological information

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Ecotoxicity Information given is based on data of the components and of similar products.

12.1. Toxicity

Toxicity The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Toxicity Not regarded as dangerous for the environment. The product is not believed to present a hazard due to its physical nature. Highly volatile.

ALCOHOLS, C9-C11, ETHOXYLATED

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1-10 mg/l,

ISOPROPANOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 48 hours: >100 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >100 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: >100 mg/l, Scenedesmus subspicatus

SODIUM NITRITE

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

d-LIMONENE

Chronic aquatic toxicity

Stikatak Carpet Stain Remover

M factor (Chronic) 1

Hexyl Cinnamic Aldehyde

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Pinenes

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Chronic aquatic toxicity

M factor (Chronic) 1

C12H24O

Chronic aquatic toxicity

M factor (Chronic) 1

Allyl Heptylate

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Camphene

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C₅₀ ≤ 1

M factor (Acute) 1

Chronic aquatic toxicity

M factor (Chronic) 1

12.2. Persistence and degradability

Persistence and degradability Biodegradable The surfactant(s) contained in this product complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct request, or at the request of a detergent manufacturer.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Persistence and degradability

The product is readily biodegradable.

ISOPROPANOL

Stikatak Carpet Stain Remover

Persistence and degradability The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Bioaccumulative potential Bioaccumulation is unlikely.

ISOPROPANOL

Bioaccumulative potential Bioaccumulation is unlikely.

Partition coefficient log Pow: 0.05

12.4. Mobility in soil

Mobility The product is soluble in water.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

ISOPROPANOL

Mobility Mobile. Soluble in water.

Surface tension 22.7 mN/m

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

ISOPROPANOL

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not puncture or incinerate, even when empty. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Stikatak Carpet Stain Remover

Waste class Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 10 (Containing hazardous residues), Empty Aerosol: 15 01 04 (No hazardous residues).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

IMDG Code segregation group	SG69, SW1, SW22
EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Stikatak Carpet Stain Remover

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824). This surfactant complies with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct request, or at the request of a detergent manufacturer.
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	ECHA: Guidance on the Compilation of safety data sheets. (V3.1, November 2015)
Authorisations (Annex XIV Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Annex XVII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification procedures according to Regulation (EC) 1272/2008	Aerosol 1 - H222, H229: Weight of evidence. Eye Irrit. 2 - H319: Calculation method.
Issued by	Technical Department
Revision date	19/02/2021
Revision	3.1
Supersedes date	15/09/2016
SDS number	22825

Stikatak Carpet Stain Remover

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated.
H272 May intensify fire; oxidiser.
H280 Contains gas under pressure; may explode if heated.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.