



Underlay Technical Specification

Item Code: TARENU11160

Issue Date: 13/10/2023

Issue No.1

Polyurethane Rebond

Suitable for stretch-fit installation of carpets

End Use Classification (BS 5808: 1991 / BS EN 14499 : 2015): L/U, Luxury Use

Standard Specifications*

Nominal density	160 kg/m³	
Nominal square weight	1849 g/m²	
Nominal roll weight	27.90 kg	
Nominal roll area	15.07m² (1.37m x 11.0m)	
Nominal thickness	11.00mm	ISO 1765

BS 5808: 1991 / EN14499 : 2015

End Use Classification	L/U, Luxury Use	
Work of compression (Min. 50 J/m² Max. 200 J/m²)	>140 J/m²	BS 4098 & ISO 2094
Retention of work of compression (min 40%)	>90 %	BS 4098 & ISO 2094
Loss in thickness after Dynamic loading (max 15%)	<5 %	BS 4052 & ISO 2094
Loss in thickness after static loading (max 15%)	<5 %	ISO 3415/3416 & BS 4939
Breaking strength (length/width) min. 40N	>90N / >40N	EN ISO 13394 BS 2576
Extension under force (length/width) max. 15%@ 30N	<10% / <10%	
Resistance to cracking (not greater than 50mm)	Pass	EN 14499 & BS 5808

Flammability

Hot metal nut test (tested in Interfloor laboratory)	Low radius of effects of ignition	BS 4790 & BS 5287
--	-----------------------------------	-------------------




Odour	No objectionable odour		
Antimicrobial and mildew resistant	Pass ASTM G21		
Colour / backing	Yellow bio-based film / 100% recycled stictchet kraft paper backing printed with vegetable-based ink		
Packaging	White bio-based or 100% post-consumer waste film / Yellow ink		
Thermal resistance	3.05 togs BS 4745		
Impact sound reduction (Delta Lw)	46dB BS EN ISO 10140 rated to BS EN ISO 717		
Emissions (US Carpet & Rug Institute)	Meets low VOC emission criteria		
Emissions (GEV Emicode)	Very low emission EC1 PLUS		
French VOC Emission Regulations	Complies A+		





Certification





Guarantee

Guaranteed for the serviceable lifetime of the carpet when used in accordance with the End Use Classification.

GREEN CREDENTIALS

Recycled Content (97.9	9%)	Sustainable Content (0.4%)		Other (1.7%)†		
Post Consumer Foam	97%	Bio-based Film	0.4%		Other	1.7%
Recycled Paper	0.9%					

[†] Sustainable options currently under development.

Notes

- The nominal roll dimensions have been quoted. These may vary slightly but will comply with the requirements of BS EN 14499:2015
- [‡] Value derived from similar product test results

THIS PRODUCT IS PRODUCED IN A FACILITY ACCREDITED TO ISO 9001, 14001 & 45001



Interfloor Ltd., Broadway, Haslingden, Rossendale, Lancashire, BB4 4LS. Tel: +44(0)1706 213131 Fax: +44(0)1706 214737 Web: www.interfloor.com International Enquiries: Telephone: +44(0)1706 238825 Fax: +44(0)1706 225114